



The Nebulae collection takes its name from the natural phenomena of interstellar clouds and their dynamic layered lighting effects. The geometric machined forms coupled with the fluid glass discs creates a balance between the elements.

The Nebulae Collection is a statement in any space and supplies a beautiful adjustable light level. The various configurations can be specified with a single glass disc or layered with an additional disc to create expansive light dispersion options. The collection is available as a wall light, pendant and various chandelier configurations.

The body is manufactured from machined aluminium white champagne or black anodised. Nebulae's discs come in a fluted clear, bubbled black, rippled blue or white pearl glass.











IMAGE /

TOP LEFT / RIGHT - NW WHITE CHAMPAGNE / WHITE PEARL, NW BLACK / RIPPLED BLUE BOTTOM LEFT / RIGHT - NW BLACK / TEXTURED BLACK, NW WHITE CHAMPAGNE / FLUTED CLEAR







Ø12" D2.5"





IMAGE /


NC11 CORDED WHITE CHAMPAGNE / FLUTED CLEAR DETAIL



NEBULAE PENDANT




NC11 CORDED
L300MM W 87MM H 590MM
L12" W 3.4" H 23"
2m CLOTH COVERED FLEX SUPPLIED



NC11 TUBE L 300MM W 87MM H 330MM^ L 12" W 3.4" H 13"^

12

[^] HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION
H INDICATES MINIMUM DROP HEIGHT (CEILING TO BOTTOM OF GLASS)







LEFT / NC12 BLACK / TEXTURED BLACK MIDDLE / NC13 OFFSET WHITE CHAMPAGNE / FLUTED CLEAR RIGHT / NC15 WHITE CHAMPAGNE / FLUTED CLEAR




NEBULAE VERTICAL CHANDELIER




NC12 L 870MM W 87MM H 300MM^ L 34" W 3.4" H 12"^




NC13 L 870MM W 300MM H 700MM^ L 34" W 12" H 28"^



NC13 OFFSET L 870MM W 300MM H 1050MM^ L 34" W 12" H 41"^



L 870MM W 870MM H 1050MM^ L 34" W 34" H 41"^



NC15 OFFSET L 870MM W 870MM H 1400MM^ L 34" W 34" H 55"^

[^] HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION
H INDICATES MINIMUM DROP HEIGHT (CEILING TO BOTTOM OF GLASS)







IMAGE /

ABOVE / NC23 BLACK/TEXTURED BLACK DETAIL LEFT / NC23 BLACK/TEXTURED BLACK





NEBULAE HORIZONTAL CHANDELIER




NC22

L 1660MM W 87MM H 300MM^

L 65" W 3.4" H 12"^


CEILING CANOPY SPACING L 678MM / 26.7"



NICOO

L1660MM W300MM H600MM^ L65" W12" H24"^

CEILING CANOPY SPACING L 678MM / 26.7"




NC24

L1660MM W300MM H600MM^

L 65" W 12" H 24"^

CEILING CANOPY SPACING L 678MM / 26.7"

25




NC34

L1660MM W1660MM H 600MM^

L 65" W 65" H 24"^

CEILING CANOPY SPACING L 678MM / 26.7"



NC35

L1660MM W1660MM H 600MM^

L65" W65" H24"^

CEILING CANOPY SPACING L 678MM / 26.7"

A HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION
H INDICATES MINIMUM HANG HEIGHT (CEILING TO BOTTOW OF GLASS)
CEILING CANOPY SPACING MEASURED FROM CENTRE-POINT OF EACH VERTICAL TUBE

24



TECHNICAL NEBULAE COLLECTION

AVAILABLE FINISHES

GLASS



CLEAR



BLACK





RIPPLED

BODY





BLACK W NODISED UMINIUM

WHITE CHAMPA ANODISED

ELECTRICAL

LAMPING

WALL LIGHT -120V / 230V - 13W LED AC MODULE, 1190 LM 2900K WARM WHITE, DIMMABLE (120V SUPPLIED FOR NORTH AMERICA/CANADA)

PENDANT / CHANDELIER 9W E27 LED, 820 LM
3000K WARM WHITE, DIMMABLE
SUPPLIED WITH AUS/NZ SALES (220-240V) ONLY
(E26 LAMP HOLDER (120V) SUPPLIED FOR NORTH AMERICA/CANADA)

LIFESPAN

WALL LIGHT = 15,000 HRS

PENDANT / CHANDELIER = 15,000 HRS

CONTROL

WALL LIGHT -

PHASE CONTROL DIMMABLE.

NETWORK CONTROL OPERATIONAL ON/OFF, NON-DIMMABLE.
DIMMING RANGE 10 - 100%. FOR OPTIMAL DIMMING PERFORMANCE WE
RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH AN
ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE
FIXTURE.

PENDANT / CHANDELIER -

PHASE CONTROL / NETWORK CONTROL DIMMABLE.
DIMMING RANGE 10 - 100%. FOR OPTIMAL DIMMING PERFORMANCE WE
RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH AN
ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE
FIXTURE.

**FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.

IP RATING

IP20 - FOR INDOOR USE ONLY.

CERTIFICATION

AS/NZS - 60598.2.1 EN - 60598.2.1 UL - 1598, CSA C22.2#250.0

MATERIALS

GLASS

EACH PIECE OF GLASS HAS BEEN PRECISELY MANUFACTURED BY LOCAL ARTISANS. AS A RESULT OF THIS PROCESS EACH SHADE HAS ITS OWN CHARACTER AND SUBTLE VARIATION.

ODY

THE ALUMINIUM BODY HAS BEEN MACHINED BY QUALITY DRIVEN LOCAL MANUFACTURERS AND THEN HAND LINISHED BY OUR IN-HOUSE WORKSHOP TECHNICIANS.

CABLE

ALL EXPOSED ELECTRICAL CABLE IS DOUBLE INSULATED AND COVERED BY A DURABLE BLACK OR WHITE CLOTH COVER.



